

ORDERING GUIDE

B100-Series

Dynamic Ratings

Distributed by AKRIBIS





B100 Series

Ordering Guide

Option	Configuration Code	Description
Base Unit ¹	B100 - X - X - X	
	B100	B100 Series Base Unit
Ethernet Communication Options		
	N	None
	L	100Base-FX Fiber Ethernet with SC connectors
	S	100Base-FX Fiber Ethernet with ST connectors
	R	100Base-T Copper Ethernet with RJ45 connector
Expansion Options (select only one option)		
	N	None
	4	Serial Communications via RS-485 SCADA
	F	Serial Communications via Fiber (ST) SCADA
	H	H ₂ Monitoring in Headspace
	O	H ₂ Monitoring in Oil
	6	Moisture Monitoring in Oil and H ₂ Monitoring in Oil
Mounting Options		
	E	IP66 (NEMA-4 Equivalent) Enclosure
	T	IP31 (NEMA-2 Equivalent) Through Panel Mount
	P	IP31 (NEMA-2 Equivalent) Surface Panel Mount
Unit with iBridge Communications ²		
	Consult Factory	

RESPONSIVE

ASSET HEALTH SOLUTIONS

¹ Each B100 Series ETM includes the following I/O: 2 x RTD, 3 x CT, 1 x Digital Input, 6 x Digital Outputs, 2 x Analog Outputs, 1 x System Alarm

² Includes one IND2000N 9 mm inductive coupler (for most power wire sizes). Couplers for other wire sizes available. Requires a new or existing receiving iBridge (CE-520) or Gateway (CE-530) for communications to control room.



An ISO 9001, ISO 14001, ISO 27001, ISO 45001 Certified Company.

Americas

+1 262 746-1230

sales.us@dynamicratings.com

Asia Pacific

+61 3 8544-0700

sales.asia@dynamicratings.com

Europe/ Africa

+44 1617 681111

sales.eu@dynamicratings.com

www.dynamicratings.com