akribis

DATASHEET

INDIGO80

Vaisala · Authorized Partner

Distributed by AKRIBIS



VAISALA

Indigo80 Handheld Indicator

For portable diagnostics



Features

- Flexible operation with Vaisala Indigo family measurement probes and other supported Vaisala devices
- Complemented by the HMP80 and DMP80 handheld probes and the GMP80P probe with pump sampling, which are optimized for portable use cases
- Intuitive user interface available in 10 languages
- Rechargeable battery
- Robust design and modern appearance
- Logged measurement data can be transferred to PC via Vaisala Insight software

Vaisala Indigo80 Handheld Indicator is an industrial-grade portable diagnostics tool. Accommodating up to two Vaisala devices, Indigo80 is ideal for spot-checking and process monitoring, as well as for configuring, troubleshooting, calibrating, and adjusting Indigo family measurement probes and other supported Vaisala devices.

Seamless compatibility for varied measurements

The Indigo80 indicator has two cable ports by which a combination of two compatible measurement devices can be simultaneously connected to the indicator. Indigo80 can communicate with most current and future Vaisala devices for measuring a wide range of parameters.

- Humidity and temperature
- Dew point
- Carbon dioxide
- Hydrogen peroxide vapor
- Moisture in oil
- Liquid concentration

For the full set of Vaisala devices currently compatible with Indigo80, see the following page. For more information on the Indigo product family, see vaisala.com/indigo.

Robust and reliable

The sturdy aluminum body of Indigo80 is resistant to chemicals and dust.

Indigo80 is powered by a rechargeable lithium-ion battery with a typical operation time of 10 h. During long-term logging Indigo80 can be powered by using an AC adapter.


Easy to use

Indigo80 has an intuitive user interface that guides the user if needed. The indicator is designed to be easy to use in numerous use cases and measurement environments.

To access logged data and configuration functionality, Indigo80 can be connected to Vaisala Insight PC software for Windows®. For more information, see vaisala.com/insight.

Multilingual user interface

Indigo80 has a multilingual, menu-based user interface that shows live measurement data both numerically and graphically. The Indigo80 user interface is available in 10 languages.



View live measurement data as numbers or graphs

Vaisala devices compatible with Indigo80

Vaisala devices with older firmware versions may have limited compatibility with the Indigo80 indicator. For the most up-to-date version compatibility information, see Firmware version compatibility of Indigo80-compatible devices Technical Note (M212901EN), available at docs.vaisala.com.

Indigo family devices	
HMP1, HMP3, HMP4, HMP5, HMP7, HMP8, HMP9, HMP80L, HMP80N probes	Humidity and temperature
TMP1 probe	Temperature
DMP1, DMP5, DMP6, DMP7, DMP8, DMP80A, DMP80B probes	Dew point
DMT153 transmitter	Dew point
GMP251, GMP252 probes	Carbon dioxide
HPP271, HPP272 probes	Vaporized hydrogen peroxide
MMP8 probe	Moisture in oil
PR53 and PR53EX series refractometers	Liquid concentration
Indigo300, Indigo510, and Indigo520 transmitters	(host devices)

Other supported devices	
HMP60, HMP63, HMP110, HMP113, HMP115 probes [1)] HMM170 module	Humidity and temperature
HMP110T, HMP115T, TMP115 probes [1)]	Temperature
GMW90 and HMW90 series transmitters	Humidity, temperature, and carbon dioxide
HMW87 and HMW87D transmitters [1)]	Humidity and temperature
HMT370EX series transmitters	Humidity and temperature
MGP241 probe	Humidity and carbon dioxide
DMT143, DMT143L transmitters	Dew point

1) Indigo80 does not support dual-device operation for these low-power devices.

Technical data

Operating environment

Operating temperature	−20 … +50 °C (−4 … +122 °F)
Storage temperature	−20 … +60 °C (−4 … +140 °F), recommended +20 °C (+68 °F)
Operating and storage humidity	20–85 %RH, when Ta ≤ +40 °C (+104 °F)
Charging temperature	0 … +45 °C (+32 …+113 °F) [1]
IP rating	IP40
Use in wet location	No
Operating environment	Indoor use
Pollution degree	3
Maximum operating altitude	2000 m (approx. 6500 ft)

1) *The battery will not charge at temperatures below 0 °C (+32 °F).*

Data logging and user interface specifications

Data logging capacity	Up to 5.5 million real-time data values
Logging interval	1 s – 12 h
Logging duration	1 min – memory full [1]
Alarm	Audible alarm function
Supported languages	English, Chinese, Finnish, French, German, Italian, Japanese, Portuguese, Spanish, Swedish
Display	2.7" sunlight readable transflective TFT LCD color display with backlight and automatic brightness control

1) *For example, data logging duration for one measurement parameter with a logging interval of one second is over eight weeks. Use an AC adapter to power Indigo80 during long-term logging.*

Battery operation time

Operation time (continuous use)	10 h at +20 °C (+68 °F) [1]
Charging time	2 hours [1]

1) *Typical value. Actual performance depends on, for example, the number and type of devices connected to Indigo80 and the data logging interval.*

Compliance

EU directives and regulations	EMC Directive (2014/30/EU) RoHS Directive (2011/65/EU) as amended by 2015/863
Electromagnetic compatibility (EMC)	IEC/EN 61326-1, industrial environment CISPR 32 / EN 55032, Class B FCC part 15 B, Class B ICES-3 / NMB-3 (Class B)
Safety	IEC/EN 61010-1
Compliance marks	CE, China RoHS, FCC, RCM, UKCA


Inputs and outputs

Max. number of connected devices	2
Connector type	M12 5-pin female (2 pcs)
Battery [1]	
Type	Rechargeable lithium-ion battery
Nominal voltage	7.2 V
Rated capacity	2900 mAh / 20.88 Wh
Charge limit voltage	8.4 V
AC adapter [2]	
Type	45 W USB-C AC adapter [3]
Connector type	USB-C
AC input	100-240 V AC, 1.2 A, 50-60 Hz
DC output	5.0 V/9.0 V/12.0 V/15.0 V DC, 3.0 A 20.0 V DC, 2.25 A 45 W
Insulation	Double or reinforced, indicated with the following symbol: ⧈
PC interface	Vaisala Insight PC software with USB-C cable (Windows OS). [4] Data can be logged and transferred also without Insight.

1) *The battery is not user-replaceable. Contact Vaisala Service Center for any battery-related maintenance needs.*
2) *The AC adapter is an optional accessory. If using an AC adapter not provided by Vaisala, make sure it fulfills the specifications given in this table and the safety requirements listed in Indigo80 Safety Guide (M212872EN), available at docs.vaisala.com.*
3) *45 W AC adapter recommended for optimal performance of Indigo80. An AC adapter with a lower power rating can also be used.*
4) *Insight software is available for download at vaisala.com/insight.*

Mechanical specifications

Weight	385 g (14 oz)
Dimensions (H × W × D)	213 × 58 × 27 mm (8.4 × 2.3 × 1.1 in)
Materials	
Main body and rear piece	Aluminum EN AW-6082 T6
Back cover	Rubber (TPE) and polycarbonate (PC), reinforced with fiberglass Flammability rating UL94 V-1
Display	Strengthened glass with anti-fingerprint (AF) and anti-reflection (AR) coatings



Indigo80 dimensions (front and side view)

Spare parts and accessories

Cables	
Cable for transmitters (M12-M8), 1.5 m (4 ft 11 in)	262195SP
Cable for probes (M12-M12), 1.5 m (4 ft 11 in)	272075SP
Flat cable for probes (M12-M12), 1 m (3 ft 3 in)	CBL210493SP
Probe connection cable (M12-M12), 10 m (32 ft 10 in)	INDIGOCABLE10M
Other	
Magnetic hanger for indicator	ASM214318SP
Weatherproof carrying case for Indigo80 and HMP80 and DMP80 series probes	ASM214759
Weatherproof carrying case for Indigo80 and a series 8 probe [1)]	ASM215318
Light carrying case for HM40S or Indigo80 indicator and a compatible probe [2)]	230245SP

1) For example, MMP8, HMP8, or DMP8 with a max. 2-m (6 ft 7 in) probe connection cable.
2) For example, DMP80, HMP80N, or GMP252 probe with handle accessory and a max. 1.5-m (4 ft 11 in) probe connection cable.

VAISALA

Published by Vaisala | B212157EN-G © Vaisala 2026

All rights reserved. Any logos and/or product names are trademarks of Vaisala or its individual partners. Any reproduction, transfer, distribution or storage of information contained in this document is strictly prohibited. All specifications — technical included — are subject to change without notice.

AKRIBIS · www.akribis.info · contacto@akribis.info