BROCHURE

LTI-HID

LogTag

Distributed by AKRIBIS

DESKTOP USB INTERFACE CRADLE

LogTag®

LTI-HID

Desktop USB Interface Cradle

AKRIBIS · www.akribis.info · contacto@akribis.info

The LogTag® LTI-HID uses interface drivers that are built into all currently supported Windows OS versions, so there is no longer any need to install proprietary drivers.

The LTI-HID is compatible with all standard LogTag® recording products having 3 silver contact pins in the lower rear case. It uses the proven and reliable spring contact arrangement taken from the LTI/USB.

*TRED30-16R and external probe in the image sold separately

Features

Downloads loggers from -20°C to +60°C.

Two indicators at the top (red & green), identify what actions the interface is currently performing.

No longer any need to install proprietary drivers.

Incorporates a micro USB socket for connection to a computer.

Applications

Industrial



Indoor Spaces

Clinic

Warehouse

Specifications

Product Model	LTI-HID
Operating Temperature Range	-20°C to +60°C
Storage Temperature Range	-40°C to +70°C
USB Standard	2.0
Environmental	IP50 (Rated for indoor use only)
Software Compatibility	LTA 2.9r2, LTA 3.0r8, LTX 1.1r1 LogTag Online
Indicators	Green 'Activity' LED. Red 'Busy/Error' LED
Power Source	Powered from computer
Size	45mm(h) x 85mm(W) x 71mm(D), excluding cable
Weight	74g, excluding cable
Case Material	Polycarbonate, ABS
Connection	USB Micro
Certifications	FCC, CE & RoHS Compliant
Accessories	1.0m USB Cable

Revision E (130721) © Copyright 2021, LogTag North America Inc. All rights reserved.
LogTag® is a registered trademark of LogTag North America Inc.
LogTag North America Inc. reserves the right to change this specification without notice.