DATASHEET

# ST10S-05

LogTag

Distributed by AKRIBIS

# CALIBRATABLE REPLACEABLE SMART PROBE

# Ultra-Low Temperature Smart Probe

## CP10S/CP11S

LogTag®

AKRIBIS · www.akribis.info · contact@akribis.info

The ultimate solution for uninterrupted temperature monitoring, the LogTag® CP10S and CP11S Smart Probes are precise and reliable probes that can be swapped out and calibrated separately from your logger.

When recalibration is needed, the plug-and-play hot-swappable design allows users to replace the probe easily. Simply disconnect the Smart Probe from your compatible logger, and plug in your new one. Calibration complete.

The expired probe can be sent to a calibration lab for re-calibration.

# Features

Plug-and-play hot-swappable calibratable probe without the need to remove the loggers from current location

Easy to download calibration certificate through LogTag® Analyzer

Battery life of 3-years

High quality gold plated MCX connector

# Compatibility Chart

| Logger Model | 1.5m Smart Probe | 3m Smart Probe |
|---|---|---|
| UTREL30-16 Dual-Channel | CP10S-15 | CP10S-30 |
| UTREL30-WiFi Dual-Channel | CP10S-15 | CP10S-30 |
| TREL30-16CP | CP11S-15 | CP11S-30 |

# Applications

Laboratories

Pharmaceutical and Vaccine

Warehouse

Cold Room

Server Room

Clinics

# Specifications

| | |
|---|---|
| **Product Model** | CP10S/CP11S |
| **Temperature Measurement Range** | -90 °C to +40 °C (-130 °F to +104 °F) |
| **Temperature Operating Range, Probe End** | -90 °C to +40 °C (-130 °F to +104 °F) |
| **Temperature Operating Range, Signal Conditioning End** | -30 °C to +60 °C (-22 °F to +140 °F) |
| **Rated Temperature Reading Accuracy** | Better than ±0.5 °C (±0.9 °F) for -20 °C to +10 °C (-4 °F to +50 °F)<br>Better than ±0.7 °C (±1.3 °F) for -50 °C to -20 °C (-58 °F to -4 °F)<br>Better than ±0.7 °C (±1.3 °F) for +10 °C to +30 °C (+50 °F to +86 °F)<br>Better than ±1 °C (±1.8 °F) for -80 °C to -50 °C (-112 °F to -58 °F)<br>Better than ±1 °C (±1.8 °F) for +30 °C to +40 °C (+86 °F to +104 °F)<br>Better than ±1.8 °C (±3.2 °F) for -90 °C to -80 °C (-130 °F to -112 °F )<br>Actual performance is typically much better than the rated values<br>Accuracy figures can be improved by recalibration |
| **Temperature Resolution** | 0.1 °C (0.2 °F) for measurements -80 °C to 0° C (-112 °F to +32 °F)<br>0.2 °C (0.4 °F) for measurements 0 °C to +18 °C (+32 °F to +64.4 °F)<br>0.2 °C (0.4 °F) for measurements –90 °C to –80 °C (–130 °F to –112 °F)<br>0.3 °C (0.5 °F) for measurements +18 °C to +30 °C (+64.4 °F to +86 °F)<br>0.5 °C (0.9 °F) for measurements +30 °C to +40 °C (+86 °F to +104 °F)<br>LogTag Analyzer® currently displays to one decimal place of °C or °F. The native resolution is what is stored in the LogTag® |
| **Acquisition Interval** | Determined by logger, shortest acquisition interval 30 seconds |
| **Sensor Reaction Time** | Based on tip, same as for current probes |
| **Environmental** | Probe tip: IP68<br>Probe tip/cable junction: IP64<br>Signal conditioning: IP44 |
| **Power Source** | CR2032 3V LiMnO2 Battery (distributor replaceable) |
| **Connection Interface** | Single wire digital interface to compatible loggers |
| **Battery Life** | 1 year storage, followed by 3 years of normal use (based on 5 minute logging) |
| **Weight** | 34g |
| **Signal Conditioning Case Material** | Polycarbonate |
| **Tip Material** | Stainless Steel 316 |
| **Probe Tip Length** | 22.5mm exposed tip |
| **Probe Tip Diameter** | 5mm |
| **Smart Probe Dimensions** | 32.5mm (H) x 46.3mm (W) x 12.5mm (D) |
| **Cable Material** | PTFE |

Revision C (19092025) © Copyright 2025, LogTag® North America Inc. All rights reserved.
LogTag® North America Inc. reserves the right to change this document without notice.
LogTag® and the distinctive shape of all LogTag® data loggers are registered trademarks of LogTag North America Inc.