BROCHURE

AHN myPette® EL³ Pipette

AHN

Distributed by AKRIBIS



ahn® *my*Pette® EL³

Manual Pipettes



NEW PRODUCT

EL³ technology uses cylindrical tip and shaft mechanism - eliminates high force to deliver much more comfortable pipetting experience

Effortless pipetting - optimal weight distribution and lowest plunger force requirement through innovative spring and seal design

Effortless tip ejection - to ensure continuous uninterrupted pipetting without any strain tip ejection

Magnet-assisted piston - consistently precise results

Effortless tip loading - for a reliable and consistent seal between the pipette and the tip without applying excessive force

Colour coding - for easy identification

Volume lock - prevents any accidental changes in the volume and guarantees constant pipetting

Large 4-digit display - Precise setting of the volume through an easy-to-read display

Highly durable material - to protect against chemical corrosion and physical stresses

Calibrated - as per ISO 8655-6

Fully autoclavable and **UV resistant**

UV RESISTANT | 3 YEARS WARRANTY | autoclavable 121°C 15 min

[1] Systematic error [2] Random error

Delivery Package	
1 pc. Manual pipette	1 pc. Shelf-mounting stand
1 pc. Conformity/calibration certificate	1 pc. Calibration tool
1 pc. Warranty card	1 pc. Silicone grease
1 pc. Instruction manual	1 pc. Sample pack of tips

Ordering information

Single Channel Pipette, Variable Volume

Volume	Colour Code	Channels	Test volume	Increments	Inaccuracy [1]	Imprecision [2]	Cat. No.
			0.25		12.00	6.00	
0.1-2.5 µL		1	1.25	0.002	2.50	1.20	8-100-32-9
			2.5		1.50	0.69	
			1		2.50	1.20	
0.5-10 µL		1	5	0.02	1.50	0.60	8-101-32-9
			10		1.00	0.40	
			2		7.00	2.00	
2-20 µL		1	10	0.02	1.50	0.50	8-102-32-9
			20		1.00	0.30	
			5		3.50	1.50	
5-50 µL		1	25	0.1	1.20	0.40	8-103-32-9
			50		0.80	0.20	
			10		3.50	1.00	
10-100 µL		1	50	0.1	0.80	0.21	8-104-32-9
			100		0.70	0.15	
			20		2.50	1.00	
20-200 µL		1	100	0.2	0.70	0.23	8-105-32-9
			200		0.70	0.15	

AKRIBIS - www.akribis.info - Measuring made easy
Uthleber Weg 14 | 99734 Nordhausen | Germany

Single Channel Pipette, Variable Volume

Volume	Colour Code	Channels	Test volume	Increments	Inaccuracy [1]	Imprecision [2]	Cat. No.
100-1000 µL		1	100 500 1000	1	2.50 0.80 0.80	0.60 0.20 0.15	8-106-32-9

Multi Channel Pipette, Variable Volume

Volume	Colour Code	Channels	Test volume	Increments	Inaccuracy [1]	Imprecision [2]	Cat. No.
0.5-10 µL		8	1 5 10	0.02	2.50 1.50 1.00	1.20 0.60 0.40	8-201-32-9
2-20 µL		8	20 100 200	0.02	2.50 0.70 0.70	1.00 0.23 0.15	8-205-32-9
5-50 µL		8	2 10 20	0.1	7.00 1.50 1.00	2.00 0.50 0.30	8-202-32-9
10-100 µL		8	10 50 100	0.1	3.50 0.80 0.70	1.00 0.21 0.15	8-204-32-9
20-200 µL		8	30 150 300	0.2	2.50 0.80 0.80	1.00 0.25 0.15	8-206-32-9
30-300 µL		8	5 25 50	0.2	3.50 1.20 0.80	1.50 0.40 0.20	8-203-32-9
0.5-10 µL		12	1 5 10	0.02	2.50 1.50 1.00	1.20 0.60 0.40	8-401-32-9
2-20 µL		12	20 100 200	0.02	2.50 0.70 0.70	1.00 0.23 0.15	8-405-32-9
5-50 µL		12	2 10 20	0.1	7.00 1.50 1.00	2.00 0.50 0.30	8-402-32-9
10-100 µL		12	10 50 100	0.1	3.50 0.80 0.70	1.00 0.21 0.15	8-404-32-9
20-200 µL		12	30 150 300	0.2	2.50 0.80 0.80	1.00 0.25 0.15	8-406-32-9
30-300 µL		12	5 25 50	0.2	3.50 1.20 0.80	1.50 0.40 0.20	8-403-32-9

[1] Systematic error [2] Random error