BROCHURE

CAPP Rondo 3D Shaker

AHN

Distributed by AKRIBIS



CAPP® Rondo

3D SHAKER

CAPP Rondo 3D Shaker operates at a variable speed range from 10 to 120 RPM. Driven by a brushless DC motor it ensures stable, quiet and maintenance-free operation, making it the right choice for applications requiring extended run sessions.

Features


- With an operational capacity of 5kg, the three-dimensional rockingand tumbling motion provides thorough homogenous mixing
- The user can save up to 9 individual protocols
- To assure total stability on the bench the shaker is equippedwith non-slip rubber feet and comes with a spiked rubber mat
- Accessories - Spiked rubber mat (included), Sticky mat (optional : Cat. No. CR3-08X-0001)



2 YEAR Warranty



Optional Attachment



Optional Attachment

Specifications

Speed	10-120 RPM in steps of 1 RPM	**Time Setting**	1-999 minutes or infinite
Load Capacity	5 kg incl. attachment	**Protection Class**	IP 21
Motor	BLDC (Brushless DC motor)	**Display**	Yes
Movement	Tumbling in fixed angle ± 7°	**Dimensions (W x D x H)**	392 x 268 x 197 mm
Plate Dimensions	350 x 350 mm	**Weight**	7kg
Pulse Mode	Yes, progammable	**Power Consumption**	17 W

Scope of Delivery

1 pc. 3D Shaker
1 pc. Power Adaptor
1 pc. Spiked Rubber Mat
1 pc. User Manual
1 pc. Warranty Card

Ordering Information

Cat. No.	Description
CR3-08X	CAPP Rondo 3D Shaker
CR3-08X-0001	Sticky mat (to be ordered separately)

AKRIBIS · www.akribis.info · contacto@akribis.info