BROCHURE

CAPP Rondo Micro centrifuge

AHN

Distributed by AKRIBIS



CAPP Rondo

MICROCENTRIFUGE

CAPPRondo Microcentrifuge has a lot more to offer than the basic microcentrifuges available on the market. It is available in two versions. The CR-68, is the basic version with a fixed speed of 6000 rpm/2000 x g. CR-68X is the advanced model with programmable speeds of up to 6000 rpm/2000 g and a timer function, which is operated via two buttons and a digital display.



Features

- Quiet and powerful operation
- Supplied with 2 interchangeable magnetic rotors and reduction adaptors
- Equipped with safety functions such as a lid safety interlock and electronic safety brake, which activates an immediate stop when the lid is opened
- Quick operation with a simple lid open/close, starts and stops in seconds
- Microprocessor-controlled digital display with speed and time indication
- Small footprint for use in hoods and at small working areas
- Magnetic rotor for easy tool-free rotor replacement

Specifications

CR-68	
Speed	6000 RPM
	2000 x g (max. RCF)
Speed Accuracy	± 300 RPM
Motor Type	DC motor
Rotor Capacity	8 x 1.5/2.0 mL. 2 x 8 x 0.2 mL
Time	No
Display	No
Dimensions (W x D x H)	162 x 157 x 116 mm
Weight	1.1kg
Power consumption	10 W
CR-68X	
Speed	1000-6000 RPM
	2000 x g (max. RCF)
Speed Accuracy	± 100 RPM
Motor Type	Brushless DC motor
Rotor Capacity	8 x 1.5/2.0 mL & 2-place PCR strip rotor
Time Setting	0 to 25 mins and infinite
Display	Yes
Dimensions (W x D x H)	162 x 157 x 116 mm
Weight	1.1kg
Power consumption	15 W

Scope of Delivery

1 pc. Microcentrifuge
1 pc. Power Adapter
1 pc. 8 x 1.5/2.0 mL Closed Micro Tube Rotor
1 pc. 2 x 8x0.2 mL PCR Strip Rotor
8 pcs. Adaptors for 0.5 mL Tubes
8 pcs. Adaptors for 0.1/0.2 mL Tubes
1 pc. User Manual
1 pc. Warranty Card

Ordering Information

Cat. No.	Description
CR-68	CAPPRondo Microcentrifuge 6000 RPM/2000 x g
CR-68X	CAPPRondo Microcentrifuge w/ adjustable speed and timer function, max. 6000 RPM/2000 x g

AHORRIS www.duplicidad.contacto@ahorris.info