BROCHURE

CAPP Solo Pipette

AHN

Distributed by AKRIBIS



CAPP Solo

SINGLE | MULTICHANNEL PIPETTES



CAPPSolo Pipettes are cost effective and robust liquid-handling tools, designed for research, clinical and academic laboratories. They are available as single and multichannel pipettes.

Features

- Very light pipette chassis reduces risk of repetitive strain injuries
- Fine-tuned to ensure high level of pipetting accuracy, precision and long-term calibration stability
- Lock counter-mechanism prevents accidental rotation while pipetting
- Exchangeable colour inserts for easy identification of pipettes by user or volume capacities
- Crafted to withstand the toughest laboratory conditions, including chemical exposure, dropping and autoclaving





2 YEAR Warranty | Fully Autoclavable | UV Resistant

Ordering Information

CAPPSolo Single Channel Pipette - Variable Volume

Cat. No.	Channel	Volume	Increments	Inaccuracy %	Imprecision %
S2-1	1	0.1-2.5 µL	0.01 µL	12.0 % / 2.5 %	6.00 % / 1.60 %
S10-1	1	0.5-10 µL	0.1 µL	2.5 % / 1.0 %	1.50 % / 0.80 %
S20-1	1	2-20 µL	0.1 µL	3.0 % / 0.9 %	2.00 % / 0.40 %
S50-1	1	5-50 µL	0.5 µL	2.0 % / 0.6 %	2.00 % / 0.30 %
S100-1	1	10-100 µL	0.5 µL	3.0 % / 0.8 %	1.50 % / 0.15 %
S200-1	1	20-200 µL	1.0 µL	2.0 % / 0.6 %	0.80 % / 0.15 %
S1000-1	1	100-1000 µL	5.0 µL	2.0 % / 0.6 %	0.70 % / 0.20 %
S5000-1	1	0.5-5 mL	50. µL	2.0 % / 0.5 %	0.60 % / 0.15 %
S5000-1-N	1	0.5-5 mL	50. µL	2.0 % / 0.5 %	0.60 % / 0.15 %
S10000-1	1	1-10 mL	100.0 µL	3.0 % / 0.6 %	0.60 % / 0.20 %
S10000-1-N	1	1-10 mL	100.0 µL	3.0 % / 0.6 %	0.60 % / 0.20 %

AKRIBIS · www.akribis.info · contacto@akribis.info

CAPPSolo Single Channel Pipette - Fixed Volume

Cat. No.	Channel	Volume	Increments	Inaccuracy %	Imprecision %
S5-1F	1	5 µL	-	1.3 %	1.20 %
S10-1F	1	10 µL	-	0.8 %	0.8 %
S20-1F	1	20 µL	-	0.6 %	0.50 %
S25-1F	1	25 µL	-	0.5 %	0.30 %
S50-1F	1	50 µL	-	0.5 %	0.30 %
S100-1F	1	100 µL	-	0.5 %	0.30 %
S200-1F	1	200 µL	-	0.4 %	0.20 %
S250-1F	1	250 µL	-	0.4 %	0.20 %
S500-1F	1	500 µL	-	0.3 %	0.20 %
S1000-1F	1	1000 µL	-	0.3 %	0.20 %
S2000-1F	1	2 mL	-	0.3 %	0.15 %
S2500-1F	1	2.5 mL	-	0.3 %	0.15 %
S5000-1F	1	5 mL	-	0.3 %	0.15 %
S10000-1F	1	10 mL	-	0.6 %	0.20 %

CAPPSolo Multichannel Pipettes

Cat. No.	Channel	Volume	Increments	Inaccuracy %	Imprecision %
S10-8	8	0.5 – 10 µL	0.1 µL	4.0 %/1.5 %	4.00 %/1.50 %
S100-8	8	10 – 100 µL	0.5 µL	3.0 %/1.0 %	2.00 %/0.70 %
S300-8	8	30 – 300 µL	1.0 µL	1.5 %/0.8 %	0.75 %/0.25 %
S10-12	12	0.5 – 10 µL	0.1 µL	4.0 %/1.5 %	4.00 %/1.50 %
S100-12	12	10 – 100 µL	0.5 µL	3.0 %/1.0 %	2.00 %/0.70 %
S300-12	12	30 – 300 µL	1.0 µL	1.5 %/0.8 %	0.75 %/0.25 %

CAPPSolo Starter Kit

Cat. No.	Description
SK-03-S01	3 pipettes S10-1 /S100-1 /S1000-1, C-05 stand, 3 racks of tips
SK-03-S02	3 pipettes S20-1 /S200-1 /S1000-1, C-05 stand, 3 racks of tips

